



Gobo Rotators

The Chroma-Q™ Junior FX Rotator accepts one gobo, fits the ETC Source 4 Junior fixture and is designed primarily for stand-alone effects projection. In addition to bi-directional 0.25-20RPM standard rotation the Junior FX Rotator features many adjustable dynamic effects including tick-tock, pendulum, shimmer, accelerate, decelerate, fire, water, rotate-pause and shake-pause. The Junior FX Rotator is supplied complete with a separate 100-240VAC power supply. Dedicated remote control units are also available.

Junior FX Rotator



Key Features

- ▶ Fits the ETC Source 4 Junior fixture.
- ▶ Operates with a single gobo.
- ▶ Designed primarily for stand-alone effects projection.
- ▶ Variable speed, bi-directional 0.25-20RPM standard rotation.
- ▶ Adjustable dynamic effects.
- ▶ Plug and play.
- ▶ Supplied complete with a separate 100-240VAC power supply.
- ▶ Dedicated remoted speed control available.
- ▶ Ultra quiet.

Junior FX Rotator Specification

Product Code	CHGR1FX	Gobo Size	M
Dimensions	79mm x 252mm x 66mm / 3.1" x 10" x 2.6"	Speed Range	0.5-25rpm
Weight	0.8kg / 1.8lbs	Power	100-240VAC, 50/60Hz, 15W, IEC chassis male

Twin FX Rotator



The Chroma-Q Twin FX Rotator fits the ETC short Source 4, Strand SL, Altman Shakespeare and Selecon Pacific fixtures. It can be operated with either one single or two counter-rotating gobos for stand-alone operation. In addition to 0.25-20RPM standard rotation the Twin FX features adjustable dynamic effects including tick-tock, pendulum, shimmer, accelerate, decelerate, fire, water, rotate-pause and shake-pause. The Twin FX Rotator is supplied with a separate 90-240VAC power supply. Dedicated remote control units are also available.

Key Features

- ▶ Fits the ETC short Source 4, Strand SL, Altman Shakespeare and Selecon Pacific fixtures.
- ▶ Can be operated with one single or two counter-rotating gobos for stand-alone operation.
- ▶ Variable speed, bi-directional 0.25-20RPM standard rotation.
- ▶ Adjustable dynamic effects.
- ▶ Supplied complete with a separate 100-240VAC power supply.
- ▶ Dedicated remote speed control available.
- ▶ Ultra quiet.

Twin FX Rotator Specification

Product Code	CHGR2FX	Gobo Size	B
Dimensions	119mm x 249mm x 69mm / 4.7" x 9.8" x 2.7"	Speed Range	0.4-25rpm
Weight	0.9kg / 2lbs	Power	100-240VAC, 50/60Hz, 15W, IEC chassis male

Featuring DMX operation, the Chroma-Q Twin FX DMX Rotator fits the ETC short Source 4, Strand SL, Altman Shakespeare and Selecon Pacific fixtures, and can be operated with either one single or two counter-rotating gobos at 0.25-20RPM. The Twin FX DMX has the added functionality of remote control via DMX & full indexing capability, allowing gobos to be reliably recalled to specific positions. The Twin FX DMX Rotator will work with the Chroma-Q PS02, PS08 and MBPS12 Magic Box™ power supplies.

Twin FX DMX Rotator



Key Features

- ▶ Fits the ETC short Source 4, Strand SL, Altman Shakespeare and Selecon Pacific fixtures.
- ▶ Can be operated with one single or two counter-rotating gobos for stand-alone operation.
- ▶ Variable speed, bi-directional 0.25-20RPM standard rotation.
- ▶ Adjustable dynamic effects.
- ▶ Works in DMX mode (with any Chroma-Q power supply) or in stand-alone mode.
- ▶ Ultra quiet.

Twin FX DMX Rotator Specification

Product Code	CHGR2DFX	Gobo Size	B
Dimensions	111mm x 263mm x 70mm / 4.4" x 10.4" x 2.8"	Speed Range	0.3-24rpm
Weight	1.2kg / 2.5lbs	Power	0.6PU (see separate PSU documentation) XLR4



The Chroma-Q 4Play™ is a fault tolerant, self healing four way DMX buffer designed to fully isolate all outputs from each other. Supplied with four 5 pin connectors, each output is separately generated and boosted from the original DMX signal. The 4Play is suitable for truss mounting with a normal hook clamp and will work with mains voltages worldwide. It also features a chassis mounted IEC male to assist international cabling.

Key Features

- ▶ 4 way DMX buffer.
- ▶ Fault tolerant, self healing.
- ▶ Each output fully isolated.
- ▶ Four 5 pin XLR connector outputs.
- ▶ One 5 pin XLR connector input and through.
- ▶ Each output is separately generated and boosted from the original DMX signal.
- ▶ Data and power indicators.
- ▶ Suitable for truss mounting with a normal hook clamp.

4Play Specification

Product Code	CHDMX4	Colour	Black
Dimensions	148mm x 158mm x 40mm / 5.9" x 6.3" x 1.6"	Power	100-240V, 50/60Hz, 15W, IEC chassis male
Weight	0.6kg / 1.3lbs	DMX Connector	XLR5 (in), XLR5 x 4 (out), XLR5 (thru)



If you have a need for a simple to operate, inexpensive eight channel DMX controller then look no further than the Chroma-Q Playback Controller. With independent Hold and Fade times for each of the 25 programmable Looks, the Chroma-Q Playback Controller is ideal for a wide range of display applications. Units can be daisy chained together for more control channels and will auto-run on power up. Separate PSU included.

Key Features

- ▶ Eight channel DMX controller.
- ▶ Inexpensive and simple to operate.
- ▶ Requires no additional hardware or software program.
- ▶ Features manually adjustable Hold and Fade times for up to 25 programmable Looks.
- ▶ Very cost-effective alternative to full lighting console.
- ▶ Ultra-compact design can be easily installed anywhere.
- ▶ Ideal for a wide variety of lighting display applications.
- ▶ Option of daisy chaining units together to provide more control channels if required.
- ▶ Auto-runs on power up.

Playback Controller Specification

Product Code	CHPBC8	Colour	Black
Dimensions	168mm x 39mm x 72mm / 6.6" x 1.5" x 2.9"	Power	100-240V, 50/60Hz, 15W, IEC chassis male
Weight	0.2kg / 0.5lbs	Control	ANSI E1.1 DMX-512A, XLR5 (out)

For the latest news and information on the Chroma-Q range, visit www.chroma-q.com



UK & International Sales
A.C. Entertainment Technologies Ltd.
Tel: +44 (0)1494 446000
Fax: +44 (0)1494 461024
sales@ac-et.com
www.ac-et.com

Northern UK Sales
A.C. Entertainment Technologies Ltd.
Tel: 0113 255 7666
Fax: 0113 255 7676
acnorth@ac-et.com
www.ac-et.com



North American Sales
A.C. Lighting Inc.
Tel: +1 416-255-9494
Fax: +1 416-255-3514
northamerica@aclighting.com
www.aclighting.com

Asian Sales
A.C. Lighting Asia KK
Tel: +81 (0)48-475-9377
Fax: +81 (0)48-475-9355
sales@aclighting.jp
www.aclighting.jp