

STAGESTAR D8+ ENTERTAINMENT HOIST



FEATURES AND BENEFITS

Lightweight and easy to transport, the CM[®] StageStar[™] D8+ electric chain hoist is built for safety and reliability in any entertainment application. Built on decades of entertainment lifting expertise, the StageStar is built to last and is easy to maintain if needed.

Capacity: 250 kg

ROBUST BODY

Engineered for the demanding needs of the entertainment industry, CM StageStar hoists feature a robust body and durable fiber reinforced composite covers that can withstand the most rigorous applications.

the brake, and motor, are easily accessible with standard tools.

EASY TO SERVICE

D8 PLUS RATING

In standard configuration, the motors are rated D8 plus in accordance with SQ P2 (2018).

This hoist is an easy-to-maintain, modular-designed device. The

gear box is maintenance-free for the whole lifetime of the hoist. All


critical parts like the chain guide and load wheel, electronic board,

Double brake is standard with CM StageStar D8 Plus electric chain hoists.

EXTENDED LIFETIME

Lifetime lubricated gearbox means no oil change is required.

Slip clutch protects all load-bearing components from overload. Designed to guarantee a safe, permanent connection between the load and the brake to meet higher safety requirements.



EASY TO SERVICE

ADAPTABLE EXTENSIONS

SAFETY

· Limit switches

Resetting the slip clutch and inspecting the brake is simple and time-saving.

 Direct control or low-voltage (24v) control available. The electronic board is easily accessible.

· Gear shaft for back-up limit switches or encoders


OTHER FEATURES:


- Swivel hook
- Operating voltage 230/400 V, 3 ph, 50 Hz
- Robust chain guide inlet to prevent chain jams
- Robust covers with ergonomic carry handles





DIMENSIONS & TECHNICAL DATA





* Dimensions in mm



Model	CM StageStar
Direct Control Product Code	192105358*
Low Voltage Control Product Code	192105359*
Capacity	250 kg (D8 Plus)
Lifting Speed at 50 Hz	4 m/min
Chain Pitch	4.0 x 12.2 mm
Power at 50 Hz	0.25kW
Current at Full Load 230 V, 50 Hz	1.30 A
Current at Full Load 400 V, 50 Hz	0.75 A
Weight Without Chain	17 kg

* Hoists with 18m chain (other chain lengths can be ordered at request), include swivel body-mounted hook, ready-mounted chain bag holder, 0.5 m power cord (LVC units include 0.5 m wired control cable).

























UK & International Sales Tel: +44 (0)1494 446000 Northern UK Sales Tel: +44 (0)113 255 7666 sales@ac-et.com www.ac-et.com