

**Panasonic**  
**CONNECT**

**PT-REQ15/PT-REZ15**  
1-Chip DLP™ Projectors

AVAILABLE FROM CY2024 Q2

Note: Release date varies depending on country or region.

# 1-Chip DLP™ Projectors Evolve with 15,000 lm<sup>1</sup> on AC 100–240 V, Unlocking Ideas for Novel Experiences



Preliminary Specification		
	PT-REQ15	PT-REZ15
Light Output	15,000 lm <sup>1</sup>	
Resolution	4K (3840 x 2400) <sup>6</sup>	WUXGA (1920 x 1200)

Product availability and release date may vary by country or region. Please contact a sales representative in your region for details.

## • Spectacular Visuals on a Grand Scale

Quad Pixel Drive<sup>2</sup> creates smooth 4K images, displays 2K/240 Hz<sup>3</sup> content without blur, and works with our ET-SWR10 Real-time Tracking Projection-Mapping System<sup>7</sup>. Rich Color Enhancer ensures accurate red for artwork, while Evolved Dynamic Contrast boosts image realism dramatically. Black-level settings offer precision point-based border adjustment for arbitrary screen shapes.

## • Effortless Workflow and Expanded Capabilities

REQ15/REZ15 expands functionality, interfaces, and options for a smoother workflow. It suits new optional lenses featuring powered center and periphery focus<sup>8</sup> and has an Intel® SDM-ready slot. The optimized optical engine enables projection at 15,000 lm<sup>1</sup> on AC 100–240 V power for efficient installation without needing electrical construction. Other highlights include user test-pattern registration<sup>9</sup>, NFC function<sup>10</sup> for setup prep without AC power, and preactivated upgrade kits for Geo Pro<sup>11</sup>.

## • Supremely Reliable Maintenance-Free Operation

Both models feature an optical engine and laser light source module compliant with the IP5X Dust Protected (IEC 60529) standard<sup>12</sup> and a refined liquid cooling system. This technology enables up to 20,000 hours<sup>13</sup> of continuous maintenance-free projection. Backup Input<sup>14</sup> and Multi Laser Drive Engine further enhance reliability and add insurance against interruptions.

<sup>1</sup> Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped. <sup>2</sup> PT-REQ15 only. <sup>3</sup> PT-REQ15 only. Supports input signals up to 1080p. The display frame rate corresponds to the input signal frame rate. <sup>4</sup> Only when the optional TY-SB01DL DIGITAL LINK Terminal Board is loaded. <sup>5</sup> Input signals to the PT-REZ15 are converted to the projector's display resolution upon playback. YPbPr 4:2:0 format only for 4K/60p signals input via DIGITAL LINK. <sup>6</sup> Maximum physical resolution with Quad Pixel Drive [ON]. <sup>7</sup> Optional ET-SWR10 is used in conjunction with third-party devices (sold separately). Compatibility with third-party devices cannot be guaranteed. Other conditions apply. <sup>8</sup> Lens release date varies depending on the model. Powered periphery focus adjustment is not supported on the ET-C15600 and ET-C11700 lenses. <sup>9</sup> Supports PNG (1/8/16/24/32/48/64-bit, non-transparent, alpha blending disabled) and BMP (1/8/24-bit) formats with a maximum resolution of 3840 x 2400 dots (PT-REQ15) or 1920 x 1200 dots (PT-REZ15). <sup>10</sup> Projectors sold in some countries or regions require an ET-NUK10 Upgrade Kit available from PASS to activate the NFC function. <sup>11</sup> Visit PASS to register your projector and download free Geometry Manager Pro software for Windows® (upgrade kits included). <sup>12</sup> The dust-proof performance of this unit is not guaranteed to be free from damage or failure under all conditions (environment with conductive dust, etc.). Please use an enclosure in environments with smoke containing oil, salt, and moisture. <sup>13</sup> Around this time, the light output will have decreased by approximately 50%. IEC62087-2:2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of airborne particulate matter. Panasonic recommends a checkup at the point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on the environment. <sup>14</sup> Terminal assignment is fixed. Input signals to primary and backup inputs must be identical.

## Specifications (Tentative)

Model	PT-REQ15	PT-REZ15	
Projector type	1-Chip DLP™ projector		
DLP™ chip	Panel size	0.8 in. diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip x 1, DLP™ projection system	
	Number of pixels	2,304,000 (1920 x 1200 pixels)	
Light source	Laser diode		
Light output <sup>1,2</sup>	15,000 lm		
Time until light output declines to 50 % <sup>3</sup>	20,000 hours (NORMAL/QUIET), 24,000 hours (ECO)		
Resolution	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)	WUXGA (1920 x 1200 pixels)	
Contrast ratio <sup>1</sup>	25,000:1 (Full On/Full Off, Dynamic Contrast [3])		
Screen size (diagonal)	70–700 inches (with supplied lens)		
Center-to-corner zone ratio <sup>1</sup>	90 %		
Lens	Optional powered zoom/focus lenses		
Lens shift (From the origin point of the lens mounter)	Vertical	±60 % (with ET-C1W400/W500/S600/T700), ±50 % (with ET-C1W300/U100)	
	Horizontal	±29 % (with ET-C1W400/W500/S600/T700), ±23 % (with ET-C1W300/U100)	
Keystone correction range	Vertical: ±40° (±5° with ET-C1U100; ±10° with ET-C1W300; ±16° with ET-C1W400; ±22° with ET-C1W500), Horizontal: ±40° (±3° with ET-C1U100; ±5° with ET-C1W300; ±10° with ET-C1W400; ±15° with ET-C1W500)		
Installation	Ceiling/floor, front/rear, free 360-degree installation		
Terminals	HDMI™ 1/2 IN	HDMI™ x 2 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input <sup>4</sup> )	
	DisplayPort™	DisplayPort™ x 1 (Deep Color, compatible with HDCP 2.3, 4K/60p signal input <sup>4</sup> )	
	MULTI SYNC IN	BNC x 1	
	MULTI SYNC OUT	BNC x 1	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)	
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control	
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	LAN	RJ-45 x 1 for network connection, PjLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible	
	USB	USB connector (Type A) x 1 for optional AJ-WM50 Series Wireless Module/USB memory	
	DC OUT	USB Type A x 1 (for power supply, DC 5 V, 2 A)	
	Expansion slot	Open slot for function boards, Intel® SDM compatible	
Protocol versions	IPv4, IPv6 <sup>5</sup>		
Power supply	AC 100–240 V, 50/60 Hz		
Power consumption <sup>6</sup>	Maximum power consumption	TBD	
	On-mode power consumption (Operating mode)	NORMAL	TBD
		ECO	TBD
		QUIET	TBD
Operation noise <sup>1</sup>	TBD		
Dimensions (W x H x D)	498 x 212 x 538 mm (19 19/32" x 8 11/32" x 21 3/16") (Without lens with feet at shortest position)		
Weight <sup>7</sup>	TBD		
Operating environment	Operating temperature: 0–45 °C (32–113 °F) <sup>8</sup> , operating humidity: 10–80 % (no condensation)		
Applicable software	Multi Monitoring & Control Software, Projector Network Setup Software, Real-Time Tracking Projection-Mapping System, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android <sup>8</sup>		
Control function via LAN	Crestron Connected™ V2, Crestron XiO Cloud™, Art-Net DMX, AMX® DD, and PjLink™ (Class 2)		

<sup>1</sup> Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is the average of all products when shipped. <sup>2</sup> When [OPERATING MODE] is set to [NORMAL]. <sup>3</sup> Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Dynamic Contrast [3], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m<sup>3</sup> of airborne particulate matter. The estimated time until light output declines to 50 % varies depending on the environment. <sup>4</sup> For the PT-REZ15, 4K signals are converted to WUXGA (1920 x 1200 pixels). <sup>5</sup> Optional AJ-WM50 Series Wireless Module is not compatible with IPv6. <sup>6</sup> Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. On-mode power consumption measured at 25 °C (77 °F) operating temperature at an altitude of 700 m (2,297 ft). <sup>7</sup> Average value. May differ depending on the actual unit. <sup>8</sup> When the optional AJ-WM50 Series wireless module is attached, the operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).

## Optional Accessories

- Zoom Lens**  
 ET-C1U100 (0.308–0.330:1)<sup>1</sup> / ET-C1W300 (0.550–0.690:1) / ET-C1W400 (0.680–0.950:1)<sup>2</sup> / ET-C1W500 (0.940–1.39:1)<sup>2</sup> / ET-C1S600 (1.36–2.10:1) / ET-C1T700 (2.07–3.38:1)<sup>2</sup>  
 Note: Lenses are equipped with Auto Lens Identification Function.  
 1 Estimated for release in CY2023 Q4.  
 2 Estimated for release in CY2023 Q3.
- Ceiling Mount Bracket**  
 ET-PKD120H (for high ceilings)  
 ET-PKD120S (for low ceilings)  
 ET-PKD130H (with 6-axis adjustment mechanism)  
 Note: ET-PKD120H/PKD120S/PKD130H is used in combination with the ET-PKD130B (sold separately).
- Function Boards**  
 12G-SDI Terminal Board  
 TY-SB01QS  
 Wireless Presentation System Receiver Board  
 TY-SB01WP  
 DIGITAL LINK Terminal Board  
 TY-SB01DL  
 12G-SDI Optical Function Board  
 TY-SB01FB  
 Note: TY-SB01FB estimated for release in CY2023 Q3.
- Attachment for Ceiling Mount Bracket**  
 ET-PKD130B
- Wireless Module**  
 AJ-WM50 Series  
 Note: Product availability may vary by country or region. The suffix at the end of the model number is omitted. Operating Temperature: 0–40 °C (32–104 °F).
- DIGITAL LINK Switcher / Digital Interface Box**  
 ET-YFB200G / ET-YFB100G  
 Note: ET-YFB200G/YFB100G is incompatible with 4K signals. Requires TY-SB01DL DIGITAL LINK Terminal Board.
- Wireless Presentation System PressIT**  
 TY-WPS1 (Basic set)  
 Note: Availability may vary by country or region.
- NFC Upgrade Kit**  
 ET-NUK10  
 Note: Product availability may vary by country or region.
- Real-Time Tracking Projection-Mapping System**  
 ET-SWR10  
 Note: For PT-REQ15 only. Availability may vary by country or region. Visit <https://panasonic.net/cns/projector/products/swr10> for more information.
- Early Warning Software**  
 ET-SWA100 Series  
 Note: Part number suffixes may differ depending on the license type.

# Panasonic CONNECT

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Availability of products and accessories may vary by country or region. Products may be subject to export control regulations. DLP, DLP logo, and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. Intel and the Intel logo are trademarks of Intel Corporation or its subsidiaries. Trademark PjLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. Windows® is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries. SOLID SHINE and PressIT are trademarks of Panasonic Holdings Corporation. All other trademarks are the property of the respective trademark owners. © Panasonic Connect Co., Ltd. 2023.



For more information about Panasonic projectors, please visit:  
 Projector Global Website – <https://panasonic.net/cns/projector/>  
 Facebook – [www.facebook.com/panasonicprojectoranddisplay](https://www.facebook.com/panasonicprojectoranddisplay)  
 YouTube – [www.youtube.com/user/PanasonicProjector](https://www.youtube.com/user/PanasonicProjector)

All information included here is valid as of June 2023.

PT-REQ15\_REZ15PRE1 Printed in Japan.