

SmartBat Wash

15x20W LED Wash Light, IP65 rated, with an RGB + Warm White LED source, wirelessly controlled with battery or wired with mains power

ORDER CODE: **SMARTBATWASH**



The **SmartBat Wash** is a high-powered LED Wash Light, that can be operated wirelessly or wired. This IP65 Wash Light has 15 x 20W RGB + Warm White LED emitters, fully calibrated to guarantee consistency, high-quality white values (CRI >93), a dynamic array of true colours with smooth colour mixing, and a powerful 10,000 lumen output. The **SmartBat Wash** is extremely flexible, and it can be used wirelessly with the built-in battery, using CRMX, W-DMX and RDM or, alternatively, wired with power and data cables, bypassing the battery, and enabling higher brightness levels. The beam angle can easily be adjustable through a magnetic beam shaper filter, allowing a wider coverage whilst keeping a high output. The **SmartBat Wash** has all the software features of the Ecl range, sharing the same user settings and capabilities.

MAIN FEATURES

- High-powered IP65 LED Wash Light, wireless (CRMX+W-DMX)/wired control, battery/AC power
- 15x20W RGB + Warm White LED source, powerful 10,000 lumen output high CRI (>93)
- Range of holographic filters that manipulate the beam angle

TECHNICAL SPECIFICATION

LIGHT SOURCE

- Source: 15x20 W RGB + Warm White LED
- Luminous flux: 4753 lm @full
- Lux: 3061 lx @5 m full
- CRI: TBD
- R9: TBD
- TLCI: TBD
- TM30 Rf: TBD
- TM30 Rg: TBD
- Source life expectancy: > 50.000 h

OPTICS

- Beam angle: 15°
- Field angle: 20°
- Additional optics: magnetic filter to achieve 25°, 40°, 60°x10°

COLOUR SYSTEM

- Colour mixing: RGBWW
- CCT: CCT control through dedicated DMX channel
- White presets: 2'800K - 10'000 K
- Colour wheel: virtual colour wheel with macros
- Macros: built-in white presets

DYNAMIC EFFECTS

- Control Resolution: 16-bit dimmer, colours
- Static mode: selection of static colour
- Manual mode: manual adjustment of colour
- Auto mode: built-in programs with execution speed adjustment
- Special features: Possible to switch OFF battery recharge through AC

BODY

- Body: sturdy die-cast aluminium body
- Body colour: RAL 9004

CONTROL

- Protocols: CRMX+W-DMX, DMX512, RDM
- Wireless Control: included, LumenRadio Timo Fx DMX/RDM compatible with both CRMX (Lumen Radio) and W-DMX (Wireless DMX)
- RDM: RDM for remote monitoring and settings
- Display: Graphic User Interface
- Firmware upgrade: yes, via USB - DMX interface (UPBOX1) not included
- IR: infrared sensor controlled by remote
- Master/Slave: for synchronised operation of more units linked in a chain
- Other: 16bit control of dimmer and colour

ELECTRONICS

- Dimmer: linear 0 ~ 100% electronic dimmer
- Dimmer curves: 4 selectable dimming modes available
- Strobe / shutter: 1 - 30 Hz, electronic
- Operating temperature: 0° ~ +45°
- LED Control: flicker free operation
- Selectable PWM: 600 ~ 25.000 Hz

ELECTRICAL

- Mains power supply: 100-240V - 50/60Hz
- Max power consumption: (TBC) 130 W
- Power factor: >0,93

BATTERY

- Battery: 16,8 V lithium
- Estimated battery life: Selectable 3h / 6h / 8h / 12h / 16h / 20 h
- Re-charge connection: magnetic fast-charge in case
- Re-charge time: 5 h/max
- Battery status: shown on display
- Other: Operation in main power without affecting battery through software battery management and charging operation in case through the quick charger connector

PHYSICAL

- IP rating: 65 for temporary outdoor application, not for fixed installations
- Cooling: passive cooling and fan-free
- Suspension and fixing: any position with quick-lock omega brackets
- Signal connection: Amphenol XLR 5p IN/OUT connectors
- Power connection: Neutrik powerCON TRUE1 IN/OUT connectors
- Dimensions (WxHxD): 381x344x143 mm
- Weight: 9,8 kg

CERTIFICATIONS / APPROVALS


- Certifications / Approvals: CE, UKCA, RCM, cTUVus, FCC

ACCESSORIES


- C6002B Slim aluminum clamp, 200kg loading, 48-51mm tubes, M10 bolt, Black
- RSR0630B Steel security cable for hanging bodies, inox steel shackle, L=60 cm, black
- 9533FXWL03 Ass. 3x2.5mm TH07 cable, SHUKO plug, MENAC3FXW socket, L.3m
- WSBBF1G5 BlackBox F-1 G5 transmitter, 2,45GHz & 5.2/5,8 GHz, DMX/RDM, 512Ch
- WSBBF1G6 BlackBox F-1 G6 transrec, 512ch, 2.45GHz, DMX&RDM,Bluetooth,G3,G4,G4S, G5, CRMX
- WSBBR512G5 BlackBox R-512 G5 receiver 512Ch, 2.45GHz & 5.8GHz, DMX/RDM optional
- WSBBR512G6 BlackBox R-512 G6 receiver 512Ch, 2.45GHz,DMX&RDM, Bluetooth,G3,G4,G4S,G5,CRMX
- FCLSMARTBATWASH Flight case for 4 SMARTBATPLUSWASH, internal AC battery charging
- SBWFILTER25/40 1060 Light diffusion filter for SMARTBATWASH, 25°/40° 10°x60°
- SBWBD Black barn door 4 directional flaps to adjust the light beam, comp. SMARTBATWASH
- SBWPOWER Single charger for SMARTBATWASH
- OS25D13 Quick-Lock omega bracket, M13 hole
- UPBOX1U Firmware uploader kit, USB IN, 3pin XLR DMX OUT, USB OUT

PRESET FULL ON

Beam angle 50%: Native



TECHICAL DRAWINGS



CERTIFICATIONS / APPROVALS



Conforms to UL STD. 1573
Certified to CSA STD: C22.2 NO. 166

Visit our website for specifications and tech documentations

