

# Arena.

# Best Connected.



**Arena offers a bigger control surface, with future-proof connectivity for larger systems.**

## Hardware Features

- 40 Playback faders
- 4 x Rotary playback encoders
- Screen-based labelling for all playback faders
- 20 Macro / Executor buttons
- Dedicated Grand Master fader
- 1 x 15.6" high-brightness touchscreen
- 1 x 7" additional touchscreen
- 3 x High-quality optical encoder wheels
- Expand control surface with optional Tiger Touch Fader Wing
- Supports one additional touchscreen
- Avokey security built-in
- Integrated UPS
- Integrated 1Gb network switch
- 1Gb OpticalCON stage link

## Physical Specification

### Unit Dimensions (w x d x h)

1072 x 428 x 150mm

### Weight

23Kg

### Flight Case Dimensions

1190 x 570 x 330

### Weight in Flight Case

44Kg

### Power Consumption

85W

### Power Specification

110 - 240V AC, 50-60Hz

### Heat Output

290 BTU/hrut

### Operating Environment

Ambient temp 0-40C / 32-104F. Max humidity 95% relative non-condensing

### Internal UPS

5 separate 5-minute periods, fully software integrated

**AVOLITES.COM**



## Software

<b>Software Platform</b> Avolites Titan	<b>DMX Channels per Device</b> 8,192	<b>Max DMX Channels per System</b> 32,768
<b>3D Visualisation</b> Capture engine built in	<b>Max Fixtures</b> Unlimited	<b>Keyframe Effect Engine</b> Custom effects with any number of keyframes
<b>Pixel Mapping</b> Animation based, video via Synergy	<b>External Control</b> Web API, MIDI, DMX, S-ACN	<b>Titan Net</b> Multi-user with any Titan console
<b>Output Formats</b> ArtNet, S-ACN, or DMX512, any combination	<b>OS</b> Microsoft Windows 10 Enterprise	

## Connectivity

<b>DMX 512</b> 8 x Neutrik 5-pin XLR, optically isolated	<b>Network</b> 4 x 1Gb Ethercon, internally switched with connection speed LEDs. 1 x OpticalCON Dual fibre 1Gb link, internally switched. 1 x 1Gb Ethercon, separately configured (network 2)	<b>Mains Power</b> IEC
<b>Data / Peripherals</b> 4 x USB 3.0, 1 front, 3 rear	<b>External Display</b> 1 x DVI-D	<b>MIDI</b> In & Out & Thru 5-pin DIN
<b>SMPTE</b> 3pin XLR	<b>Switch Trigger</b> ¼" jack	<b>Audio In</b> ¼" stereo jack

**AVOLITES.COM**