

Cameras

## HDBaseT PTZ Camera for HS-1500T and HS-1600T PTC-140T

|                                  |   |
|----------------------------------|---|
| Video format/Resolution          | 1080p 60/59.94/50/30/29.97/25<br>1080i 60/59.94/50<br>720p 60/59.94/50                      |
| Image Sensor                     | 1/2.8 inch high quality HD CMOS sensor  |
| Effective Pixels (approx.)       | 2.07 Mega pixels  |
| S/N Ratio                        | >55dB   |
| Min. Illumination                | 0.5Lux (F1.8, AGC ON)   |
| Electronic Shutter               | Auto / Manual   |
| Zoom Ratio                       | 20x Optical Zoom, 10x Digital Zoom  |
| Gamma Control                    | Off / Normal  |
| Iris Control                     | Auto / Manual   |
| Digital Noise Reductions         | Yes   |
| On-Screen Display (OSD)          | English, Simplified Chinese   |
| White Balance                    | Auto, Manual, One Push, 3000K, 4000K, 5000K, 6500K  |
| AGC / Gain Control               | Auto / Manual   |
| Mirror / Flip Image              | Yes   |
| Focus Mode                       | Auto / Manual   |
| Panning / Tilting Range          | Pan: 340° , Tilt: +90° to -30°  |
| Panning / Tilting Speed          | Pan: 0.1~60°/sec<br>Tilt: 0.1~30°/sec   |
| Preset                           | 255 Position  |
| Focal Length                     | f=5.2 (wide) to 98 (tele) mm<br>F1.6 to F3.5  |
| Field of View (Horizontal, Wide) | Approx. 54.7° (WIDE END) / 3.3° (TELE END)  |
| Image Compensation               | Backlight Compensation  |
| Video Output                     | HDBaseT (PoE) x1<br>RJ-45 x1  |
| Audio Input                      | 3.5mm Line in   |
| Tally LED                        | Dual color (Red, Green)   |
| Lens Filter                      | M52.0 x 0.75 Thread with UV Protection  |
| Control Protocol                 | VISCA, Pelco-D, Pelco-P, DVIP   |
| Remote Control Interface         | RS-232<br>Lan (RJ-45)<br>HDBaseT(RJ-45)/Serial control on Receiver Box: Transmit up to 100m |
| Video Compression Format         | H.264, H.265, Dual stream output  |
| Audio Compression Format         | AAC/MP3/G.711A Audio compression  |

|                                    |  |
|------------------------------------|--|
| Audio Bitrate                      | 96Kbps, 128Kbps, 256Kbps   |
| HD IP Interface                    | 100M IP port(100BASE-TX); Support DVIP   |
| Streaming Protocols                | TCP/IP, HTTP, RTSP, RTMP(S), DHCP, SRT, Multicast, etc   |
| First Stream Supported Resolution  | ----   |
| Second Stream Supported Resolution | ----   |
| Video Bitrate                      | ----   |
| Video Bitrate Mode                 | ----   |
| Encoding Frame rate                | ----   |
| POE                                | ----   |
| F/W Update                         | Ethernet   |
| IR Control                         | Yes  |
| Camera Control Unit                | HS-1500T/HS-1600T series/RMC-180 series/RMC-300 series/PTZ View Assist APP   |
| Tripod Mount                       | 1/4-20 UNC   |
| Optional Accessories               | WM-1/ WM-10/ WM-11   |
| Color                              | Black/White  |
| Dimension (LxWxH)                  | 156 x 184 x 186 mm   |
| Weight                             | 1.6 kg   |
| Operating Temp. Range              | 0~40 °C  |
| Power                              | DC 12V 12W   |
| What's in the Box                  | 1 x PTC-140T Unit<br>1 x IR remote controller<br>1 x PTC-140T Thank You Card<br>1 x Ceiling mount bracket-A<br>1 x Ceiling mount bracket-B<br>6 x Ceiling mount bracket screw M3*4mm<br>1 x DC 12V Power Adaptor<br>1 x Power Cord<br>1 x A braided safety cable<br>1 x RS-232 DB9 9 Pin to 8 Pin Mini DIN Cable |